

FO 55 - PARKING SENSOR PROTECTORS

Technical Data Sheet

Product description

Parking Sensor Pads are designed to mask the sensors during car body repairs. The pre-cut pad is suitable for most type of cars and is easy to apply. FO 55 is paintable and easy to remove.

Construction

- Adhesive	Silicone adhesive
- Carrier	PET
- Color	Red

Applications

- Especially designed for masking parking sensors during car body repairs

Technical details

Diameter	18 mm
Thickness	0,09 mm
Adhesive strength	9,5 N/25mm
Service temperature range	-40°C up to +180°C
Elongation	90%
Solvent resistance	Good
Moisture resistance	Good

Recommendations for use

Temperature: between +10°C and +49°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of one year.

Packaging

- 150 Individual protectors / Box
- 50 Boxes / Case

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.

670 New York Street
Memphis, TN 38104 USA
Tel. : 800-261-7976 Fax : 901-274-8816
sales@chemicar.com - www.chemicar.com.com

CHEMICAR^{usa}