

Trim Masking Tape

Description:

This is a premium quality tape for masking of rubber parts. It allows paint to flow under the molding. The tape is easy to handle and quick in application. Its high flexibility and adhesion, combined with moisture absorbing crepe backing ensures perfect paint results.

Recommendations for Use:

- Masking rubber around flush fitted car windows
- Masking rubber around sun roofs
- Masking gaps between body parts

Application:

Best applied at temperatures between +50°F and + 120°F. Surface must be clean and free from dust and grease. Avoid touching exposed adhesive surface of the tape, as this impairs the performance. Pressure sensitive adhesive must be applied with a maximum pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hrs. at 72°F.

Storage and Shelf Life:

Clean and dry in a well ventilated area, preferably at a temperature between 50°F and 86°F. Stored under these conditions shelf life will be a minimum of 1 year.

Specifications:

Adhesive	Rubber Adhesive
Adhesion	4.5 N/cm
Tensile Strength	41 N/cm
Elongation	11%
Service temperature range	-30°F -> + 212°F
Solvent resistance	Good
Moisture resistance	Good
Pet Film	10 mm
Size	50 mm x 10 m (10mm plastic strip)
Carrier	Slightly creped paper with PET- film enforced
	Glassine paper
	Thickness: 0.19 mm



The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar USA cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the products suitability for their own applications.