

Parking Sensor Protectors

Description:

FOL55 Parking Sensor Protectors are designed to mask the sensors during car bumper repairs. This pre-cut cover fits most types of vehicles and is easy to apply. FOL55 is paintable and easy to remove.

Application:

- Designed for masking parking sensors during car bumper repair and polishing
- Use with solvent and water based paint
- High temp resistant



Recommendations for Use:

Best applied at temperatures between 10°C/50°F and 49°C/120°F. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with maximum of pressure in order to achieve maximum adhesion level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C/74°F.

Storage and Shelf Life:

Store in a clean, dry and well ventilated area between 10°C/50°F and 30°C/86°F. Stored under these conditions shelf life will be a minimum of one year.

Specifications	
Adhesive	Silicone
Carrier	PET
Color	Red
Diameter	18 mm
Thickness	0.09 mm
Adhesive strength	9.5 N/25mm
Service temp range	-40°C/-40°F up to 180°C/356°F
Elongation	90%
Solvent resistance	Good
Moisture resistance	Good
Part # FOL55	150 individual protectors per box (50 boxes per case)

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar USA cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.