

Fleece Wire Harness Tape

Description:

This textile protective tape has especially been designed for manual cable harness production typical for the passenger compartment. It is abrasive resistant, noise reducing, resistant to aging and not self-extinguishing.

Provides abrasion protection and prevents rattles and squeaks.



Application:

Best applied at temperatures between +50°F and + 122°F. Surface must be clean and free from dust and grease. Avoid touching exposed adhesive surface of the tape, as this impairs the performance. Pressure sensitive adhesive must be applied with a maximum pressure in order to achieve maximum adhesion. The indicated level of performance will be reached after a bonding period of 24 hrs. at 23°C/75°F.

Recommendations for Use:

- Manual cable harness for the passenger compartment-headliner-doors-trunk of vehicles.
- Not for use in engine compartment.

Storage and Shelf Life:

Clean and dry in a well ventilated area, preferably at a temperature between 50°F and 86°F. Stored under these conditions shelf life will be a minimum of 1 year.

Specifications:

Total Thickness	0.3 mm
Adhesive	Rubber adhesive
Adhesive Strength	1.5 N/cm
Elongation at Break	10-25%
Tensile Strength	40 N/cm
Temperature Resistance	110°C/230°F
Carrier	PET fleece textile
Color	Black
Size	0.75 inches x 25 yards

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar USA cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the products suitability for their own applications.