

TRAILER FLOOR COATING

For full protection and longevity of this coating, use **1 gallon per 48 sq²** applied in **2 or 3 thick coats**. Optimal strength will be obtained at: 1/32 inch or 0.7-1 mm or 30-40 mils.

Protect your investment fully, do not skimp on product application!

TRAILER	SQ FEET	FLOOR ONLY	RAMP ONLY
5 x 8	40 ft ²	3 Qts	2 Qts
5 x 10	50 ft ²	1 Gal	2 Qts
6 x 10	60 ft ²	1 Gal + 1 Qt	3 Qts
6 x 12	72 ft ²	1 Gal + 2 Qts	3 Qts
6 x 14	84 ft ²	1 Gal + 3 Qts	3 Qts
7 x 14	98 ft ²	2 Gal	1 Gal
7 x 16	112 ft ²	2 Gal + 2 Qts	1 Gal
8.5 x 18	153 ft ²	3 Gal + 1 Qt	1 Gal + 1 Qt
8.5 x 20	170 ft ²	3 Gal + 2 Qts	1 Gal + 1 Qt
8.5 x 24	204 ft ²	4 Gal + 1 Qt	1 Gal + 1 Qt

***FOR V NOSE TRAILERS – ADD 1 QUART**